

FlexDSX®

Cross-Connect Family



The FlexDSX® chassis accommodates four-port jack cards with dual monitor ports. Utilizing these dual monitor ports, technicians save time by monitoring both sides of a circuit from a single test access point.

The modular FlexDSX components include the dual monitor jack, four-pack module and the chassis.

Features and Benefits

- **Four-port jack cards**
Dual monitor ports enable circuit monitoring in both directions.
- **Staggered jack alignment**
Supports industry-standard patch cords
- **Up to 84 circuits in a six-inch chassis**
Increased bay density
- **Integrated cable management**
Jumper rings and rear cable bars are installed on the skeleton bay
- **IN/OUT cable terminations on the backplane**
Provides multiple circuit count configurations



FlexDSX Front Cross-Connect Products

Ordering Information

Description	Catalog Number
FlexDSX front cross-connect products	
FlexDSX front cross-connect 7' skeleton bay, 23" mounting, holds 10 chassis	DFX-B7S001
FlexDSX 56-circuit loaded DSX panel; dual monitoring 19"/23" (14- 4 packs)	DFX-100056
FlexDSX 64-circuit loaded DSX panel; dual monitoring 19"/23" (14- 4 packs)	DFX-100064
FlexDSX 84-circuit loaded DSX panel; dual monitoring 23" (21- 4 packs)	DFX-100084
FlexDSX empty chassis; 84-circuit (21- 4 packs)	DFX-9T0001
FlexDSX 4-pack with dual monitoring jacks	DFX-9T1000

FlexDSX Rear Cross-Connect Products

Ordering Information

Description	Catalog Number
FlexDSX rear cross-connect products	
FlexDSX rear cross-connect skeleton bay, 23" mounting, holds 14 chassis (84-circuit)	DMB-77WC01
FlexDSX rear cross-connect 84-circuit loaded 23" DSX panel	DFX-100084R

FlexDSX Cross-Connect Accessories

Quality patch cords and cross-connect cables in various configurations and lengths

Ordering Information

Description	Catalog Number
Bantam patch cords	
Three-conductor single	
0.3 m (1')	PJ712
0.92 m (3')	PJ716
1.83 m (6')	PJ722
3.66 m (12')	PJ1212
6.1 m (20')	PJ1420
Three-conductor dual	
0.3 m (1')	PJ762
0.92 m (3')	PJ766
1.83 m (6')	PJ772
3.66 m (12')	PJ1312
6.1 m (20')	PJ1520
Bantam plugs	
Three-conductor looping plug	PJ746
Three-conductor dummy plug	PJ748
100 Ohm termination plug	PJ800
Circuit guard plug-red	PJ925R
Central office cable	
26 AWG dual shield FTP riser cable, 28-pair equivalent to 1249C series	DSR-28261DDGYXX*
22 AWG dual shield FTP riser cable, 28-pair equivalent to 616C series	DSR-28222SDGYXX*
Manual wire-wrap tool kit	AUX-0X0165
Cross-connect wire	
304 m (1000')	DSX-CCW/1000

*To designate reel length, replace XX as follows

02 = 304 m (1000 ft)

04 = 609 m (2000 ft)

05 = 762 m (2500 ft)

06 = 914 m (3000 ft)

10 = 1524 m (5000 ft)



Website: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080

Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our website.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

104232AE 8/07 Revision © 2007 ADC Telecommunications, Inc. All Rights Reserved